

SELECTAir/ BEE

EASY TO OPERATE,
GOOD SEALING EFFECT



PRODUCT INTRODUCTION

- The new SelectAir/Bee is a compact, efficient & dual-functional air cushion machine which inflates air pillow and air bubble on site and suitable for industrial used. Its outstanding feature is the extended guide rod which fits the 400mm width of air cushion film and the average speed could reach 20-23m/min. The multifunctional operation panel can realize various operation modes to meet your variety of packaging needs.
- The key feature of the air cushion machine SelectAir/Bee is not only its speed, but also its modern outlook and sealing system. It's running with heating wire instead of heating block. This will only take a few seconds to start the machine upon switching on the power. The internal hot-melt belt is used for heat insulation and transmission.
- The SelectAir/Bee is very suitable for industrial and some large-scale express transportation, medium and large logistics enterprises, as well as other industries. It's easy to use and low maintenance, and having one air packing machine can realize various of packaging needs without increasing your cost, in fact, reduce your packaging cost.





ACCESSORIES

- Rewinder System Air Cushion Basket
- Overhead Hopper Film Delivery System
- Movable Basket For Air Cushion Film

ADVANTAGE

- Touch Panel, easy to operate , multi-functional intelligent setting
- External foot pedal to improve packaging operation
- Freely adjust the air volume, temperature, length, and mode selection
- No air leakage, good sealing effect
- One machine can accommodate various specifications of air cushion film, 200mm, 400mm, 600mm, etc.
- Improve efficiency and reduce costs



TEL: 400-9988-122

WEBSITE: www.selectpacktech.com

E-MAIL: sales@selectpacktech.com

HEADOFFICE ADDRESS:

No.1050,Linxian Road,Tinglin Town, Jinshan District, Shanghai, China

SOUTHEAST ASIA BRANCH:

No.10, Jalan Industri USJ1/18 , Taman Perindustrian USJ 1, 47600 Subang Jaya, Selangor Darul Eshan, Malaysia

Model	SelectAir/Bee
Size	540x370x360mm
Film Application	200mm*20μm*1200m, 400mm*20μm*600m
Speed	25m/min
Power	300W
Voltage	110V-220V
N.W.	7kg
G.W.	10kg